

Sloan Retrofit Urinals Replace Existing Urinals

Sloan SU-1209 Top Mount, Retrofit Urinal

- Complete HEU (high efficiency urinal) flushing from .125 to 0.5 GPF.
- Vitreous china, white-color with large foot print to cover old caulk lines.
- 3/4" top spud flush valve connection for Sloan manual or automatic valve.
- Washdown flushing action and 2" NPT outlet flange.
- All mounting hardware and hanging bracket included - Carrier not included.
- Flush volume is determined by the Flushometer installed on the urinal.
- Compliant to applicable sections of ASME A112.19.2/CSA B45.1
- Integral flushing rim and vandal resistant strainer.
- Fully interchangeable with the obsolete Sloan models SU-1200-A, -1202-A & -1205-A



Model	Description	Ship Lbs.	Order No.
SU-1209-A	Sloan Retrofit Urinal , top mount 3/4" spud, 0.125 to 0.50 GPF	76.0	SN2004
G2-8186	Sloan G2 8186-0.50 battery operated flush valve, 0.50 GPF	9.5	SN1164
G2-8186	Sloan G2 8186-0.25 battery operated flush valve, 0.25 GPF	9.5	SN1164E
G2-8186	Sloan G2 8186-0.125 battery operated flush valve, 0.125 GPF	9.5	SN1164H



Sloan SU-1210, -1215 Rear Spud, Retrofit Urinal

- Complete HEU (high efficiency urinal) flushing from .125 to 0.5 GPF.
- Vitreous china, white-color with large foot print to cover old caulk lines.
- 3/4" rear spud flush valve connection.
- Washdown flushing action and 2" NPT outlet flange.
- All mounting hardware and hanging bracket included - Carrier not included.
- Flush volume is determined by the Flushometer installed on the urinal.
- Compliant to applicable sections of ASME A112.19.2/CSA B45.1
- Integral flushing rim and vandal resistant strainer.

Model	Description	Ship Lbs.	Order No.
SU-1210	Retrofit Urinal, 3/4" rear spud, 0.125 GPF design	87.0	SN2006
SU-1215	Retrofit Urinal, 3/4" rear spud, 0.50 GPF design	87.0	SN2006E

Sloan Small Urinals, Top Spud & Rear Spud Models: SU-7009 and SU-7019

- Complete HEU (high efficiency urinal) flushing from .125 to 0.5 GPF.
- Vitreous china, white-color: SU-7009 has a 3/4" top spud flush valve connection; SU-7019 has a 3/4" rear spud flush valve connection.
- Washdown flushing action and 2" NPT outlet flange on both models
- All mounting hardware included - Carrier not included.
- Flush volume is determined by the Flushometer installed on the urinal.
- Compliant to applicable sections of ASME A112.19.2/CSA B45.1
- Integral flushing rim and vandal resistant strainer.



Model	Description	Ship Lbs.	Order No.
SU-7009	Small Urinal, 3/4" top spud, 0.125 to 0.50 GPF design	70.0	SN2008
SU-7019	Small Urinal, 3/4" rear spud, 0.125 to 0.50 GPF design	70.0	SN2008E
G2-8186	Sloan G2 8186-0.50 top spud flush valve, 0.50 GPF	9.5	SN1164
G2-8186	Sloan G2 8186-0.125 top spud flush valve, 0.125 GPF	9.5	SN1164H